

Below is a **partial list** of available **hot melt products**. We offer many other products in each category to meet your specific requirements. We will recommend and sample the appropriate product for your application and testing process. If you require additional assistance in selecting the proper adhesive please contact techsupport@amsalesinc.net Or submit the [adhesive request form](#) or call **1-800-382-6108**.

PACKAGING-Case/Carton Sealing
(sample listing)

AMS3723	1010cps	Amber	Fast Set	Low Cost-general purpose packaging- good heat resistance
AMS3724	1000cps	Amber	Fast Set	General purpose-high heat resistance- for tougher board stock
AMS4004	1300cps	Amber	Fast Set	Freezer grade with fast set speed-aggressive tack-case & carton stock
AMS3725	1125cps	White	Med Set	Low Temp Application 250-275F-good heat resistance
TS100Supra	1200cps	Clear	Fast Set	NEW lower application temperature-275-325F-NO CHARRING

ASSEMBLY
(sample listing)

AMS3017	1450cps	White	Slow Set	Long open time hot melt for a large variety of assembly applications. Excellent adhesion to foam, fabric and various paper substrates. Application equipment: Manual & Automatic Tank Systems or Hot Melt Wheel Coaters.
AMS3943	2600cps	Amber	Slow Set	Long open time hot melt adhesive designed for assembly applications. It is used for bonding paper, foam, fabric, fiberglass, wood and metal. It has very high heat resistance, aggressive tack, excellent adhesion and good heat stability. Application methods include bead, spray or wheel coater systems.

PRESSURE SENSITIVE (tacky)
(sample listing)

AMS6550	1800cps	Amber		Low viscosity pressure sensitive with excellent cold temperature Adhesion to polyethylene and many other substrates. Application Methods include bead, spray or wheel coater systems.
AMS6551	2400cps	Water-White		Low viscosity pressure sensitive assembly adhesive, with high peel strength and aggressive tack. Ideal when color clarity is needed. application methods include bead, spray or wheel coater systems.
AMS6552	9500cps	Light Amber		Higher viscosity pressure sensitive for product assembly applications. Excellent balance of tack and higher heat resistance. Ideal application

method is bead or wheel coater systems.

AMS6553 5200cps Amber

Medium viscosity pressure sensitive with high tack at low temperatures
Excellent bleed through resistance. Economical label and assembly
adhesive. Application methods include bead, spray or wheel coater
systems.

REMOVABLE-FUGITIVE

(sample listing)

AMS1421 2000cps Clear

Very low staining removable or fugitive hot melt. It has a long open
time, low tack and low peel. **Prime recommendation**

AMS3848 850cps Light Yellow

Low viscosity with a **moderate tack**, long open time and low peel.

AMS5267 2700cps Amber

Standard recommendation for a **repositionable** PSA label. Good quick
tack with moderate bond strength, can be die cut.