

HMT® Benchmark

Product Assembly

System Specifications

Model #	205-LV	215-HV	315-HP	525/535-HP
Voltage	120v	120v	120v	120v
Tank Capacity*	8 Lbs	15 lbs.	15 Lbs	25/35 lbs
Hose/Gun (Bead)	2	2	1	2
Hose/Gun (Spray)	1	1	1	2
Hose Length	up to 16 Ft.	up to 16 Ft.	up to 20 Ft.	up to 24 Ft.
Max. Viscosity, cps.	10,000	10,000	100,000	100,000
Melt Rate*	10 lbs/hr	10 lbs/hr	15 lbs/hr	25 lbs/hr
Pump Rate*	44 lbs/hr	44 lbs/hr	60 lbs/hr	60 lbs/hr
Temp Control Range	350°F	250° – 375°F	100° – 450°F	100° – 450°F
Sensor Style	RTD	RTD	RTD	RTD
Readout	None	Tank	All Zone	All Zone

Standard Features

Over Temp Shut-Off	•	•	•	•
Pump Ready Lock-Out	•	•	•	•
Tank Filter	•	•	•	•
Auto-Off Timer			•	•
Auto-Standby Timer			•	•
Wake-up Timer			•	•
Manual Standby			•	•

Recommended Guns

DG-400 Handguns	•	•	•	•
DG-500 Handguns	•	•	•	•
AV-600 Single Valve	•	•	•	•
AV-600 Multi-Valve			•	•

Recommended Nozzles

Single Bead Nozzles	•	•	•	•
Slot Nozzles			•	•
Spray Nozzles	•	•	•	•